

RM190A

RM SERIES INDUSTRIAL RACK MOUNT LCD DISPLAY

LCD Display	19.0" TFT Active Matrix Panel
Max. Resolution	1280 x 1024 SXGA@75Hz
Pixel Pitch(mm)	0.294(H) x 0.294(V)
Brightness	300 cd/m2
Contrast Ratio	800:1
Back Light	4 CCFL
Display Area	376 x 301mm
Response Time	5ms(Typ.)
Display Colors	16.7M
Viewing Angle	170 (H), 170 (V)
VGA Input Signal	RGB Analog 0.7V Peak to Peak
Signal Connector	15 Pin D-sub for VGA RCA Video in, S-Video
OSD Control	Power Switch, Menu, Select (+,-),Auto Front OSD Control
Operating Temperature	0° ~ 50° C
Storage Temperature	-20° ~ 60° C
Power Consumption	40W
Power Supply	External Power Adapter
Safety	CE, FCC, TUV-GS, UL Compliant
Front Bezel	Option: Protection metal frame
Mounting	Rack mount, VESA Mount (VESA 75/100)
Handle	Silver Chrome, Height 110 mm, Diameter 10 mm
LCD Protection	Zief®, High Contrast, 5mm Vandel glass, Tempered Proof, Purple Tinted
Touch Screen	Option Resistive/Capacitive/SAW touch sensor
Dimension	483 x 396 x 67 (mm)
Height	9U
Weight	15.5 lbs



ISO 9001:2008

ACCUVIEW INC.

Tel: 800.275.4255 Fax: 201.440.5655 Address: 40C Cotters Lane, Suite F, East Brunswick, NJ 08816 Email: sales@accuview.com

*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2012 Accuview Inc. All rights reserved.

WWW.ACCUVIEW.COM